DOUBLE ACTING "FLEXIBLE" TRAFFIC DOOR

W. CLEAR .160 PVC TEXTURED FLEXIBLE ABUSE PLATES (STANDARD)	I.C. 3" OVERLAP VINYL PROTECTIVE EDGE WRAP CLEAR .160 PVC TEXTURED FLEXIBLE ABUSE PLATES (STANDARD)	HO Nors to be constructed from a base layer of .160 Clear P.V.C. Standard features are: • 100 • 101 • 102	National Descense Sales@nationalaccessdesign.com S13-331-3400 fax: 866-300-4539 sales@nationalaccessdesign.com NationalAccessDesign.com NationalAccessDesign.com DOOR SPECIFICATION
SDSS (STND.) STAINLESS STEEL	cancellations to v responsibility for	ssumed by buyer for changes or work in process. Buyer hereby accepts all sizes and dimensions. This order ssed until all acknowledgement forms eturned.	NAD-2200 FLEX DOOR JOB NAME/LOCATION CUSTOMER/LOCATION
DATED: 2/19/2024	Specification according by Date:	epted by:	CUST. ORDER NO. CUST. PO ORDER NO.

	ACCESS J DOC ALLC 513-351-3400 fax: 866-300-4539 sales@nationalaccessdesign.com NationalAccessDesign.com			
	DOOR SPECIFICATION			
	Opening Width x Height			
	Qty			
	BI-PARTING SINGLE PANEL			
	L R			
	TEXTURED P.V.C. COLOR OPTIONS			
	🗆 BLACK 🗖 BLUE			
	BROWN OYSTER GREY			
s.	OPTIONS FOR AIR PRESSURE			
	CLOSING MAGNETS			